## AXXICON CHECK LIST FOR AIM MIRROR *AXXICON* www.axxicon.com **Axxicon Quotation Number Revision Number** Company name \_\_\_ Date Country Agent Contact Person Contact Person Email **Email** MIRROR FIXED HALF SPECIFICATIONS Mirror surface plate, polished N0/N1 (SPI-SPE 1-2) according ISO 1302 One Temperature sensor is mounted at Pos. C. Sensor has 5 meters cable length o Mirror FH o Mirror FH Special (including position A and B for pressure measuring) Please specify temperature sensor type: o J-type: (FE) o K-type: (CuNi) MOULD TEMPERATURE **NOZZLE AND BACKSIDE RADIUS** o 10-140 (Low temperature - water) O Standard radius on mirror: 35mm o 140-200 (High temperature - oil) o Radius of nozzle: COATING \* MATERIALS o None o Material: Tin coating o Fillers: o MCP coating PRESSURE MEASURING (to be filled out for mirror FH special) Pos. A: measurement on Runner o Hole with dummy plug; Ø 4 mm o Pressure sensor Kistler 6157BA 0,4mtr o Pressure/Temp. sensor Kistler 6191Q01 0,4mtr Pos. A o Extention cable for Kistler sensor 5,0 mtr o Other: Pos. B: measurement on Product Specimen o Hole with dummy plug; Ø 4 mm o Pressure sensor Kistler 6157BA 0,4mtr Pos. C o Pressure/Temp, sensor Kistler 6191Q01 0.4mtr o Extention cable for Kistler sensor 5,0 mtr o Other: **NOTE** All AIM parts will be tested with a material selected by Axxicon Pos. B Standard material PP or PE \* For add on prices, please refer to price list REMARKS

Please return this data sheet to your local agent or to: a.lavrijsen@axxicon.com or r.matulessy @axxicon.com